SPECIFICATIONS / PERFORMANCE DATA

ELECTRICAL DATA

VOLTS HZ PH AMPS RPM HP
115 60 1 .52 3250 1/40
Motor Type = Permanent Split Capacitor, Impedance Protected
PERFORMANCE DATA
Flow Range 0 – 10 GPM
Head Range 0 – 9 Feet
Minimum Fluid Temp 40º F
Maximum Fluid Temp 220º F
Maximum Working Pressure 125 Psi
Minimum Inlet Pressure 14 Psi
Dimensions 6”H x 7”W x 8”L
Weight (Shipped) 10.5 lbs
Connection Sizes Inlet / Outlet ½”
Monthly Operating Cost 14 kWh / $1
Cord Length 9 Feet
Cord Style 3 prong Flush Surface
Typical Life 8 + years
OPERATING MODES

Automatic (with included timer)

Manual (using wireless remote option)
Full (without any control device installed)
Sound Activated (using optional device)
Motion Sensor Activated (using optional device)
Push-Button On-D’mand (using optional wireless device)
98 Event / 7 Day Custom By-Day Schedule (Optional Timer)
Foot Stepper Switch (using optional control device)
X-10 Home Automation Control (using optional device)
 Pipe Freeze Protection Mode (Setting Temp Dial)