# SPECIFICATION DATA

#### 1. Product Name

VERSI-FOAM® Systems 10 and 33 Disposable Foam Kit

#### 2. Manufacturer

RHH FOAM SYSTEMS, INC. 6001 South Pennsylvania Avenue

Cudahy WI 53110 USA

Telephone: 1-800-657-0702 414-744-6066

FAX: 414-744-8227

E-Mail: sales@rhhfoamsystems.com Web Site: www.rhhfoamsystems.com

## 3. Product Description

VERSI-FOAM® Systems 10 and 33 are disposable foam kits that contains two chemical components - Component A (isocyanate) and Component B (polyol blend); patented U-CONTROL dispensing gun, ten (10) multi-purpose mixing nozzles, and packet of petroleum jelly. It requires no external power source.

### 4. Technical Data

VERSI-FOAM Systems 10 and 33have the following physical properties:

DENSITY:	2.8 pounds per cubic foot, free rise	ASTM D1622
R FACTOR:	7.00	ASTM C518
COMPRESSIVE STRENGTH:	37 psi (parallel)	ASTM D1621
WATER ABSORPTION:	2.3%	ASTM D2842
CLOSED CELL CONTENT:	>90%	ASTM D2856
DIMENSIONAL STABILITY:		ASTM D2126

% Volume Change, 158° F, 100% Humidity. 2 wks -4.00% % Volume Change, -20° F, 7 days -2.00%

HIGH TEMPERATURE TOLERANCE 250° F LOW TEMPERATURE TOLERANCE -250° F

FLAMESPREAD: N/A ASTM E84 SMOKE DEVELOPED: N/A ASTM E84

YIELD: System 10 10 cubic feet or 120 square feet at 1" thickness

System 33 33 cubic feet or 396 square feet @ 1" thickness

TACK FREE TIME: 30 seconds RISE TIME: 30 seconds