US & CA

GreenGuard

For use in replacement siding operations to provide a level surface over old siding, add insulation and weather protection

Kingspan®

Description

Kingspan GreenGuard® XP14 Siding Underlayment comprises ¼" thick closed-cell polystyrene (XPS) with perforated capsheets on both sides.

facers on both sides. It is lightweight, easy to cut, and install. It is designed to be used as a "leveling board," adding insulation and moisture protection in installation of new vinyl siding over old siding. It is available

GreenGuard® XFP14 Siding

.

Panel rigidity, water-resistance, durability, easy cutting and excellent

underlayment.

Compliance

Intertek CCRR-1022;
CA BEARHFTI Lic. No. T 1506;
Canada CCMC 12764-R;
UL Listings - R11183

Handling & Storage

When stored outdoors, XPS should be protected from exposure to direct sunlight using the original packaging or an opaque, light–colored tarp. XPS that has been unwrapped should be covered or rewrapped. XPS left exposed should be covered within 60 days to minimize UV damage. Once the exposed XPS is covered, the damage stops and is limited to the thin layer of cells on the surface that was exposed to the UV. XPS cells below the UV exposed surface layer are generally undamaged and the XPS overall performance remains intact.

WARNING: This product is combustible. A protective barrier or thermal

storage and installation.

Health & Safety

Kingspan GreenGuard® XP14 and XFP14 Siding Underlayment are made of synthetic materials that are generally not recognized as providing a food source for insects, fungus, mold or mildew. It should always be properly installed and stored. For detailed safe handling and safety information, refer to product SDS.

The product should not be used as an exposed interior surface in buildings

barrier, such as ½" gypsum wallboard or equivalent, should be applied between this product and the interior of such buildings. Fire and building codes should be followed.

retarders to avoid condensation and subsequent damage to structures (ASHRAE Handbook of Fundamentals). Since foam sheathings are non-structural, they must be installed over adequately braced framing in accordance with local building codes.

WARNING: Do not stand on or otherwise support your weight on this product unless it is fully supported by a load bearing surface.

Property	Test Method	Value	
		Kingspan GreenGuard® XP14 Siding Underlayment	Kingspan GreenGuard® XFP14