

Penetrating Sealer, Pifolds et al

MULTI-PURPOSE PRIMER FOR POROUS AND NON-POROUS SURFACES

NOTE Proper bond and preparation

DESCRIPTION

PRIMER STX 100™ is a premium concentrated acrylic primer for use over various interior substrates, including concrete, sheet vinyl, well bonded VCT/VAT, cutback adhesive residue, gypsum underlayment, terrazzo, epoxy floor coatings, wood, ceramic, quarry tile, and metal. Its unique ability to bond to both porous and non-porous substrates makes it ideal for varying jobsite conditions. PRIMER STX 100™ is very easy to use; it creates an extremely tenacious bond to the substrate and reduces surface porosity.

APPLICATIONS

Suitable for use on all interior residential, commercial, and institutional applications

Use as a bonding agent between multiple lifts of self-leveling underlayments

Can be used as a primer for porous or non-porous substrates

ADVANTAGES

Excellent alkali resistance

Can be applied to a variety of substrates

High solids content, very low odor

Non-flammable, non-toxic, non-explosive

Water-based and no VOC's

Low particle size for excellent penetration

Can be applied using 1:1:1 mixing method

Will bond tenaciously to any well bonded and clean substrate

Will not contribute to the growth of mold or mildew

No dangerous emissions or irritating fumes

Environmentally friendly. May be LEED eligible; visit www.penetransp.com for LEED contributions document

SHELF LIFE / STORAGE

12 months from the date of manufacture, when unopened, undamaged original container is properly stored in a cool, dry place, unexposed to moisture and sunlight. Always tightly reseal container after use. **DO NOT ALLOW TO FREEZE!**

PACKAGING

1-gallon (3.8-l) pails; 5-gallon (19-l) pails

PRIMER STX 100™