DESCRIPTION

[illegible]

APPLICATIONS

[illegible]

ADVANTAGES

[illegible]

SHELF LIFE / STORAGE

[illegible]

PACKAGING

[illegible]

TECHNICAL DATA

Approximate coverage (Yield) per 25-lb (11.3-kg) bag:

[illegible]

Installation thickness:

[illegible]

Application temperature range:

[illegible]

Set (ASTM C191; 70°F (21°C), 50% RH):

[illegible]

Color:

[illegible]

Accepts coverings (70°F (21°C), 50% RH):

[illegible]

DIRECTIONS FOR USE

Surface preparation:

[illegible]

[illegible]

C[illegible]: [illegible]

[illegible]: [illegible]

[illegible]: [illegible] 3/4 (2 [illegible] & [illegible] 1, [illegible] /3 0), [illegible]

A[illegible]: T[illegible] L[illegible] [illegible], [illegible]

E: [illegible]

Mixing:

L[illegible] T[illegible] L[illegible] 10-1 [illegible] 0 (21), [illegible] 3 [illegible] 1 [illegible]

[illegible] T[illegible] 1/2 [illegible] T[illegible] L[illegible]

Installation:

T[illegible] L[illegible]

S[illegible]f [illegible]: [illegible] T[illegible] L[illegible] 1/2 (13[illegible]) [illegible]

E[illegible] S FI SK : L[illegible] 3 [illegible] 1 [illegible] 1/4 ([illegible])[illegible]

Ac[illegible] -SK S[illegible] l : [illegible] L[illegible] 2, [illegible] & [illegible] 3. ([illegible])031([illegible])4([illegible])-13 [illegible]

TW*[prt2 TD nsbeaø, cvnh0 Prysubsnet(ed1ppn)106(SpecfultyW*,